

OfficePrint PS-300UP

3 Port 10/100 Print Server (2-USB2.0 + 1-Parallel Port)

Overview

The external print servers enhance capability by letting you place your printers at convenient locations directly on the Ethernet network, and by increasing network printer performance and management. The print servers support the Simple Network Management Protocol (SNMP), which remote printer management and a warning. A standard SNMP agent is permanent on these print servers. Any standard SNMP-based application can be used to access and manage these print servers.



Specifications

Interface	<ul style="list-style-type: none"> • Parallel: 1 D-type 25 pin female port, supporting bi-directional communication • USB: 2 USB2.0-compliant port, supporting 1.5Mbps (low speed), 12Mbps (full speed) and 480Mbps (high speed) data transmission rate. This port automatically detects the make and model of the USB printer. • LAN: Compliant with IEEE 802.3/802.3u standard, 10/100Mbps auto-sensing, RJ-45 (UTP) connector
Software	<ul style="list-style-type: none"> • Easy-to-use Setup Wizard • Network Operating System Support: Windows 95/98/98SE/Me, Windows NT 4.0/2000/XP/2003, Mac OS 8.1 or higher, UNIX/Linux, NetWare (Bindery/NDS) • Network Protocol Support: TCP/IP, IPX, NetBEUI, AppleTalk, LPR, SMB over IP*, RAW TCP, IPP • Parallel port printing mode: ECP • Windows Print Monitor Technology • DHCP Client Support • Management: <ol style="list-style-type: none"> 1. Web interface 2. Windows-based Setup Program 3. Telnet • SNMP Support • HP WebJetAdmin Support • Email Alert • Job Log Support • Firmware Upgradeable

Hardware	CPU: RDC 2886 Flash: 1 Mbps System Memory: 2Mbytes SDRAM Parallel Port: 1 D-type 25 pin female port, supporting bi-directional communication USB Port: 2*USB2.0 standard compliant port LAN Port: 10/100Mbps, auto-sensing Reset Button: Reset / Power On Load Factory Defaults Power Supply: 5V 2A
Weight	255g(device only)
Dimension	180(L) * 100(W) * 35(H) mm
Regulatory Compliance	CE / FCC Class B
Operating Temperature	0 ~ 50°C
Storage Temperature	-5 ~ 65 °C
Operating Humidity	0 ~ 70%
Storage Humidity	0 ~ 80%

LED Indicator

LED Indicator	Counter	Remark
Power	1	Green
Status	1	RED
LAN 10/100	2 (G/Y)	Green for 100, Yellow for 10
Parallel port	1	Green
USB port 1	2 (G/Y)	Green for Hi-Speed, Yellow for other
USB port 2	2 (G/Y)	Green for Hi-Speed, Yellow for other

Ordering Information

PS-300UP : 3 Port Print Server (2*USB 2.0+1*Parallel)

** Product specification subject to change without notice.*

Toplink C&C Corporation

3F, No. 4, Lane 609, Sec. 5, Chung Hsin Rd.,
 San Chung City, Taipei Hsien 241, Taiwan, R. O. C.
 Email: sales@linkpro.com.tw Tel: 886-2-22789851 (REP.)
<http://www.linkpro.com.tw>