

Office Print PS-360A

3 Port 10/100 Multi-protocol Print Server

Overview

The external print servers enhance capability by letting you place your printers at convenient locations directly on the Ethernet network, and by increasing network printer performance and management. The print servers support the Simple Network Management Protocol (SNMP), which remote printer management and a warning. A standard SNMP agent is permanent on these print servers. Any standard SNMP-based application can be used to access and manage these print servers.



Specifications

Interface	<ul style="list-style-type: none"> Parallel: 3 DB-25-pin female Centronic port, supporting bi-directional communication LAN: Compliant with IEEE 802.3/802.3u standard, 10/100Mbps auto-sensing, RJ-45 (UTP) connector
Software	<ul style="list-style-type: none"> Easy-to-use Setup Wizard (Windows-based Setup CD) Network Operating System Support: Windows 95/98/98SE/Me, Windows NT 4.0/2000/XP/2003, Mac OS 8.1 or higher, UNIX/Linux, NetWare (Bindery/NDS) Network Protocol Support: TCP/IP, IPX, NetBEUI, AppleTalk, LPR, SMB over IP Internet Printing Protocol (IPP) Support: Yes Windows Print Monitor Technology: Yes DHCP (client) Support: Yes Default IP Address: 192.168.0.10; DHCP: off Print Job Log: Yes Management: 1. Web interface 2. Windows-based Setup Program Software Upgradeable <ol style="list-style-type: none"> 1. Web interface 2. Windows-based Setup Program 3. TFTP SNMP & HP Web JetAdmin Support: Yes
Hardware	<p>CPU: High-performance RISC-cored SoC processor</p> <p>Flash: 1MBytes</p> <p>System Memory: 2Mbytes SDRAM</p> <p>Parallel Port: 3* DB-25-pin female Centronic port, supporting bi-directional communication</p> <p>LAN Port: 10/100Mbps, auto-sensing, RJ-45(UTP) connector</p> <p>Reset Button: Yes</p>

Toplink C&C Corporation

3F, No. 4, Lane 609, Sec. 5, Chung Hsin Rd.,
 San Chung City, Taipei Hsien 241, Taiwan, R.O.C.
 Email: sales@linkpro.com.tw Tel: 886-2-22789851 (REP.)
<http://www.linkpro.com.tw>

	Dimension: 228 (Length) x 137 (Width) x 36(Height) mm Power Supply: 5V, 2A
Weight	340g(device only)
Regulatory Compliance	CE / FCC Class B
Operating Temperature	0 ~ 50°C; Storage : -5 ~ 65 °C
Operating Humidity	0 ~ 70%; Storage : 0 ~ 80%

LED Indicator

LED Light	Position	Type	Color	Specification
Power	Side	SMT	Uni-color, Red	a. When the power is supplied OK, it goes on. b. When no power or power supply is NOT OK, it goes off.
Status	Top	SMT	Uni-color, Green	a. When powered on, it flashes for the P.O.S.T. b. When in Upgrade Mode, it flashes slowly. c. When being upgraded, it flashes quickly.
LAN Link	Side	SMT	Uni-Color, Green	a. When the cable (Link) is OK, it goes on. b. If the cable (Link) is NOT OK, it goes off.

Ordering Information

PS-360A : 3-Parallel-port 10/100 Multi-protocol Print server

** Product specification subject to change without notice.*